

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863200 - LA-DL-LUNA2-WW

LED Downlighters

</productimages/863200.jpg>

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Built-in
Colour temperature (K)	3000 - 3000
Colour of light adjustable	No
Rated luminous flux according to IEC 62722-2-1 (lm)	2200
(lm)	0 - 2200
Nominal current (mA)	110 - 700
Nominal voltage (V)	36 - 36
Voltage type	DC
Max. system power (W)	26
Energy efficiency class of the light source according to EU regulation 2019/2015	F
Beam angle	Extreme wide beam >80°
Built-in depth (mm)	107
Height/depth (mm)	134
Outer diameter (mm)	173
Built-in diameter (mm)	162 - 162
Housing colour	Aluminium
Degree of protection (IP), front side	IP20
IP20	
Degree of protection (IP)	IP20
Suitable for ceiling mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	1 - 26
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for built-in mounting	Yes
Optics	Reflector
No	
(cm)	100
Number of poles	2
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes