

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

Led armatuur plafond inbouw

Package type: CT á 1 pce

/productimages/866085.jpg



PRODUCT SPECIFICATIONS:

| | |
|--|---|
| Spot | |
| Mounting method | Built-in |
| Colour temperature (K) | 3000 - 3000 |
| Colour of light adjustable | No |
| Nominal current (mA) | 0 - 700 |
| Nominal voltage (V) | 3 - 3 |
| Voltage type | DC |
| Max. system power (W) | 2.1 |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | F |
| Beam angle | Medium beam 21-40° |
| Beam angle (°) | 44 |
| Built-in depth (mm) | 50 |
| Height/depth (mm) | 52 |
| Outer diameter (mm) | 42 |
| Built-in diameter (mm) | 36 - 36 |
| Housing colour | Stainless steel |
| Degree of protection (IP), front side | IP44 |
| Other | |
| Suitable for ceiling mounting | Yes |
| Suitable for lamp power (W) | 2.1 - 2.1 |
| Suitable for clamp-mounting | Yes |
| Adjustability | not adjustable |
| Lamp type | LED not exchangeable |
| With light source | Yes |
| Electrical connection with connector system | Yes |
| Type of control gear | LED operating device current-controlled |
| With control gear | No |
| Colour of light | White |
| Housing material | Aluminium |
| Light sharing | Symmetric |
| Colour rendering index CRI | 80-89 |
| Suitable for built-in mounting | Yes |
| Optics | Lens |
| Material cover | Plastic, transparent |
| Light distributor | Focal lens |
| Light outlet | Direct |
| Number of poles | 2 |
| Colour consistency (McAdam ellipse) | SDCM2 |
| With mounting bracket | No |
| With presence indicator | No |



Dimmable

Yes

