

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

Led armatuur plafond inbouw

Package type: CT á 1 pce

/productimages/866090.jpg



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	6000 - 6000
Colour of light adjustable	No
Nominal current (mA)	0 - 700
Nominal voltage (V)	3 - 3
Voltage type	DC
Max. system power (W)	2.1
Energy efficiency class of the light source according to EU regulation 2019/2015	G
Beam angle	Wide beam 41-80°
Beam angle (°)	60
Built-in depth (mm)	50
Height/depth (mm)	52
Outer diameter (mm)	42
Built-in diameter (mm)	37 - 37
Housing colour	Aluminium
Degree of protection (IP), front side	IP44
Other	
Suitable for ceiling mounting	Yes
Suitable for lamp power (W)	2.1 - 2.1
Suitable for clamp-mounting	Yes
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for built-in mounting	Yes
Optics	Lens
Material cover	Plastic, opal
Light distributor	Diffuser lens/optic/panel
Light outlet	Direct
Number of poles	2
Colour consistency (McAdam ellipse)	SDCM2
With mounting bracket	No
With presence indicator	No



Dimmable

Yes

