

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870464.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Bus system KNX	No
Bus system KNX-RF (Radio Frequent)	No
Bus system radio frequent	No
Bus system LON	No
Other bus systems	Other
Radio frequent bidirectional	No
Model	Presence detector
Mounting method	Flush mounted (plaster)
Material	Plastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
With bus connection	Yes
Substation input	Yes
Optimum mounting height (m)	3
Max. reach sideways (m)	5.55
Max. reach frontally (m)	5.55
Diameter reach on floor (m)	11.11
Number of channels	1
DALI-2 certified	No
Min. depth of built-in installation box (mm)	32
Width (mm)	12
Height (mm)	32
Diameter (mm)	50
Built-in diameter (mm)	12
(V)	15 - 28
Switching current (mA)	10
Voltage type	DC
Max. mounting height (m)	5
Yes	
Suitable for ceiling mounting	Yes
Suitable for wall mounting	No
Voltage supply over bus	Yes
No	
With connection cable	No