

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: [info@klemko.nl](mailto:info@klemko.nl)

# klemko®

/productimages/876693.jpg

**Led spots. inbouw**

Package type: BX á 1 pce



## PRODUCT SPECIFICATIONS:

|                                                                                  |                                         |
|----------------------------------------------------------------------------------|-----------------------------------------|
| Spot                                                                             |                                         |
| Dimmable                                                                         | Yes                                     |
| Colour temperature (K)                                                           | 2700 - 2700                             |
| Colour of light adjustable                                                       | No                                      |
| Rated luminous flux according to IEC 62722-2-1 (lm)                              | 215                                     |
| (lm)                                                                             | 0 - 215                                 |
| (lm/W)                                                                           | 0 - 102                                 |
| Nominal current (mA)                                                             | 0 - 700                                 |
| Nominal voltage (V)                                                              | 3 - 3                                   |
| Voltage type                                                                     | DC                                      |
| Max. system power (W)                                                            | 2.1                                     |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | E                                       |
| Beam angle                                                                       | Extreme wide beam >80°                  |
| Beam angle (°)                                                                   | 90                                      |
| Built-in height (mm)                                                             | 13.7 - 13.7                             |
| Height/depth (mm)                                                                | 15                                      |
| Outer diameter (mm)                                                              | 65                                      |
| Built-in diameter (mm)                                                           | 61 - 61                                 |
| Housing colour                                                                   | Aluminium                               |
| Degree of protection (IP), front side                                            | IP44                                    |
| Other                                                                            |                                         |
| Degree of protection (IP)                                                        | IP44                                    |
| Luminous flux adjustable                                                         | Continuously variable                   |
| Suitable for lamp power (W)                                                      | 2.1 - 2.1                               |
| Adjustability                                                                    | not adjustable                          |
| Lamp type                                                                        | LED not exchangeable                    |
| With light source                                                                | Yes                                     |
| Electrical connection with connector system                                      | Yes                                     |
| Type of control gear                                                             | LED operating device current-controlled |
| With control gear                                                                | No                                      |
| Colour of light                                                                  | White                                   |
| Housing material                                                                 | Aluminium                               |
| Light sharing                                                                    | Symmetric                               |
| Colour rendering index CRI                                                       | 80-89                                   |
| Suitable for surface mounting                                                    | Yes                                     |
| Suitable for built-in mounting (cm)                                              | Yes                                     |
| Light distributor                                                                | 200                                     |
| Light outlet                                                                     | Diffuser lens/optic/panel               |
| Number of poles                                                                  | Direct                                  |
|                                                                                  | 2                                       |



With presence indicator

No

